



**Air Mesh** - High-breathable and  
resistant inner lining

Wear-resistance microfibre  
reinforcement



## JUMP 925

### L55266 2AF

STANDARD	SIZE
S3 SRC	38/47
COLORI	WEIGHT
Black	635 gr
ELECTRIC CATEGORY	FIT
Antistatic	10,5

#### COMPONENTS:

**Upper:**  
**Upper lining:**  
**Toe-cap:**

Water-resistant nubuck and protective TPU toe-cap.

Breathable mesh fabric.

- Aluminum toe-cap.
- Impact protection 200 Joules.
- Compression protection 1,500 kg.

#### Anti-puncture insole:

Made of anti-perforation, absorbent, abrasion- and flakingresistant fabric.

#### Sole:

Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.

#### Tread:

High density, non-slip (SRC), abrasion- and hydrocarbonresistant.

#### Midsole:

Low-density, comfortable and shockproof.

#### RECOMMENDED USES



Deep self-cleaning  
grooves

Non-slip grooves  
for ladders

HSA - Maximum heel  
shock-absorption

**Punto Flex** - Special  
technical solution that allows  
the foot to bend correctly



**Stabilizer** - Stabilizer arch  
inside the sole for correct foot  
movement



#### MODEL DESCRIPTION:

Mid shoe with anti-puncture fabric, water-resistant nubuck upper and protective TPU toe-cap. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.

#### RECOMMENDED USES:

Industry in general, engineering, construction, warehouses, agriculture.

#### USE AND MAINTENANCE:

Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.