


**CUT  
LEVEL  
C**

### Type of use (\*)

Thanks to its technical characteristics, this glove is suitable for all major works requiring dexterity and a significant protection against mechanical risks including cut (cut level C, as per EN388 European standard). Industrial maintenance, automotive assembly, general handling, making cables, cardboard factory, metal sheet manufacture, aircraft assembly. Handling fibreboards, blocks...

### Technical features

- ✓ **Construction:** Seamless knitter liner. Elasticated knitted wrist. HDPE fibres (High Density Polyethylene).
- ✓ **Colour:** grey/black.
- ✓ **Gauge:** 13.
- ✓ **Coating:** Soft crinkle latex coating on palm. Open back (ventilated).
- ✓ **Sizes:** 9 to 11.
- ✓ **Packing:** - Carton of 100 pairs.  
- Bundle of 10 pairs.



Learn more: [www.singer.fr](http://www.singer.fr)



### Advantages

- ✓ These gloves provide excellent cut resistance while providing greater dexterity and comfort.
- ✓ This product provides good protection against cut and tear in dry conditions handling.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ Excellent grip in dry conditions for safe and secure handling.

### Conformity

This glove has been tested according to the following European standards:

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.

It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). Category II.

EU type examination certificate (module B) issued by the **CTC**, notified body **n°0075**.

EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels PHD5LAT	EN 388 : 2016
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>3</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>X</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>4</b>	
Puncture resistance (in Newtons)	20	60	100	150	-	<b>2</b>	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level PHD5LAT
	2	5	10	15	22	30	<b>C</b>

«X means that the glove has not been submitted to the test.



**3 X 4 2 C**

Your distributor **SINGER® SAFETY**

**SINGER®** safety