



EVASPORTB



EVASPORTN / EVASPORTAB

>> Type of uses (\*)

As protection against mechanical risks: projections of solids, of chips, particles, shocks ...  
Grinding, industry, sport, laboratories, assembly shops. woodworking, polishing. Protection against UV rays.

>> Technical features

- ✓ **Style:** Spectacles with adjustable sidearms. (4 positions).
- ✓ **Treatment:** UV protection. Anti-scratch treatment.
- ✓ **Lens:** clear polycarbonate. Thickness 2.00 mm.
- ✓ **Frame and temples:** polyamide.
- ✓ **Screw:** nickel.
- ✓ **Frame colour:** blue.....EVASPORTB  
black.....EVASPORTN  
black anti-fog.....EVASPORTNAB
- ✓ **Dimensions:** (width) 150 mm x (height) 55 mm.  
(between the two sidearms) 100 mm +/- 10 mm.
- ✓ **Weight:** 34 grams.
- ✓ **Packing:**
  - carton of 100 units.
  - box of 10 units (minimum of order).
  - each unit under individual polybag.



Learn more: [www.singer.fr](http://www.singer.fr)

>> Advantages

- ✓ ISO9001 manufacturing ensuring a reliable and durable quality.
- ✓ Adjustable temple to fit distinct face profile.
- ✓ Safety clear side shields.
- ✓ Single-piece lens fit perfectly on different face contours and offer wide vision.
- ✓ Molded-in nose bridge provides uncompromised comfort and fit.
- ✓ Perforated temples will allow the use of adjustable safety cord.



>> Conformity

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.
- ✓ **EN 170: 2002.** Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (**module B**) issued by **BSI** (Netherlands). Notified body **n°2797.**

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection	Symbol <b>FT</b>	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 6 mm and a minimum mass of 0.86 g launched at 45 m/s).
Optical quality	Symbol <b>1</b>	Class 1: continuous works (better quality).
Scale number	Symbol <b>2C.1.2</b>	Colour perception: not impaired Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor. This applies to UVC and most UVB radiation <sup>(b)</sup> . Typical source <sup>(a)</sup> : Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps. <small>(a) The example given for typical source is for general guidance. (b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm &amp; 100 nm to 280 nm for UVC).</small>

Your distributor **SINGER® SAFETY**

