



[Premium!]

>> Use (*)

Thanks to its technical characteristics, this device is particularly suitable for all major works requiring protection against mechanical risks, liquid splashes namely: industry, mechanical workshops, scouring, automotive industry, agriculture, forestry development, facade renovation, work in a quarry, carpentry, maintenance of parks and gardens, painting, laboratory ...

>> Technical features

- ✓ Wide safety goggle.
- ✓ Black TPU frame.
- ✓ Soft foam seal all around the mask edge for a high level of comfort and a perfect fit.
- ✓ Wide easy adjustable headband.
- ✓ Curved clear lens with anti-scratch and anti-fog special high resistant treatment.
- ✓ Weight: 125 g.
- ✓ Packing: - carton of 54 units.
- bundle of 6 units.

Learn more www.singer.fr

>> Advantages

- ✓ The curved shape of this google provides a perfect fit of the equipement to all faces for a better comfort, less fatigue and wide vision.
- ✓ Wide foam edge will give comfort and will absorb the sweat of the user.
- ✓ It delivers greater protection from dust, debris, and small particles to penetrate into the mask.
- ✓ Extra-wide and adjustable elastic headband for more comfort and secure fit.



>> Conformity

This product has been tested according to the following European Standards:

- ✓ **EN 166: 2001.** Personal eye-protection. Specifications.
- ✓ **EN 170: 2002.** Personal eye-protection. Ultraviolet filters. Transmittance requirements and recommended use.

It complies with the European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (**module B**) issued by **CERTOTICCA**. Notified body n°0530.

Download the EU declaration of conformity on: <http://docs.singer.fr>



Mechanical protection (EN166)	Symbol BT	Impact resistant against high speed particles at high temperatures (corresponds to the impact of a steel ball with a diameter of 0.86g launched at 120 m/s).
Fields of application (EN166)	Symbol 3 Symbol 4	Liquids (droplets or projection). Large dust particles > 5µm.
Optical quality (EN166)	Symbol 1	Class 1 continuous works (better quality).
Scale number (EN170)	Symbol 2.1.2	Colour perception: not impaired Typical application: for use with sources that emit UV radiation predominantly at wavelengths < 313 nm and when glare is not an important factor. This applies to UVC and most UVB radiation ^(b) . Typical source ^(a) : Low pressure mercury vapour lamps, such as those used to stimulate fluorescent or "black lights", actinic and germicidal lamps. (a) The example given for typical source is for general guidance. (b) The wavelengths of these bands are recommended by IEC (that is UVB 280 nm to 315 nm & 100 nm to 280 nm for UVC).

Your distributor **SINGER® SAFETY**

SINGER® safety