



Type of use

Thanks to its technical characteristics, this glove is particularly suitable for all major works requiring good dexterity in dry environments. General handling with tools, handling raw materials, machine operator, outdoor works (gardening, lawn care, landscaping), assembly and construction, bricklayers, roofers, plumbers.. (*)

Technical features

- ✓ **Construction:** knitted seamless pattern. Knitted wrist. Liner in polyester fibres.
- ✓ **Gauge:** 13.
- ✓ **Coating:** latex coating on palm. Open back.
- ✓ **Colour:** black coating, black liner.
- ✓ **Sizes:** 9, 10, 11.
- ✓ **Packing:** - carton of 100 pairs. - bundle of 10 pairs.



Learn more: www.singer.fr



Advantages

- ✓ **Seamless construction:** improves user comfort (will avoid rough points and consequently the risks of reddening or irritation of the skin). Improves dexterity for easy handling of small parts and reduces hand fatigue.
- ✓ **Elasticated knitted wrist** for a better comfort and a perfect fit of the glove on the hand.
- ✓ **Protective coating:** crinkle latex coating provides high levels of grip for safe and secure handling.
- ✓ The back of the glove uncoated allowing the hand to breathe.

Be careful, people sensitive to latex should avoid contact with this material.



Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by the **CTC**, notified body **n°0075**.

EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels NYM73LN		EN 388 : 2016 3 1 3 1 X
Abrasion resistance (number of cycles)	100	500	2000	8000	-	3		
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1		
Tear resistance (in Newtons)	10	25	50	75	-	3		
Puncture resistance (in Newtons)	20	60	100	150	-	1		
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level NYM73LN	
	2	5	10	15	22	30	X	

«X means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

