



>> Type of use (*)

Thanks to its technical characteristics, this glove is particularly suitable for all major works requiring abrasion and tear resistance as for handling construction materials.

Ideal for builders, roofers, carpenters, tilers, masons, gardeners, farmers, handling fibreboards, blocks...

>> General features

- ✓ **Construction:** cut and sewn pattern. knitted wrist. Open back.
- ✓ **Materials:** 100% cotton interlock liner.
Heavy crinkle latex coating on palm and back (knuckle coating version). With **Actifresh®**.
- ✓ **Colour:** natural colour liner / green coating.
- ✓ **Sizes:** 7, 8, 9, 10.
- ✓ **Packing:** - Cartons of 100 pairs.
- Bundles of 10 pairs.



More information: www.singer.fr



>> Advantages

- ✓ The guarantee and benefits of an **ISO 9001** certified manufacturing: quality of products, regularity...
- ✓ cotton interlock liner: brings the comfort of a natural material which facilitates the absorption of perspiration
- ✓ Protective coating: the latex coating will bring you additional protection and excellent grip during handling in wet conditions.
- ✓ Open back style allows excellent breathability.
- ✓ Anti-bacterial effect of the Actifresh® treatment deprives bacteria from developing and growing.
The Actifresh® treatment is effective against bacteria, fungi, rust, stains and algae in preventing these micro-organisms from developing. It promotes a longer life and avoids the creation of bad odours.
- ✓ Knitted wrist for a snug fit.

>> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>

EN 388: 2016. Protective gloves against mechanical risks								EN 388 : 2016 2 1 3 1 X
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels	▼	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	2		
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	1		
Tear resistance (in Newtons)	10	25	50	75	-	3		
Perforation resistance (in Newtons)	20	60	100	150	-	1		
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level	
	2	5	10	15	22	30	X	

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue LS_2018_12_18. Copyright Singer.