



### >> Type of use (\*)

Thanks to its technical features, this glove is particularly suitable for all heavy works requiring good strength as well as good resistances in oily and / or fatty environments: automobile assembly, automobile repair, construction, public works, metal works, raw material handling, sharp handling sheets, household refuse collection, handling abrasive materials, deep sea fishing, maintenance of public parks...

### >> General features

- ✓ **Construction, materials:** cut and sewn pattern. 100% brushed cotton liner. Heavy nitrile knuckle coating. Open back. Knitted wrist. **With Actifresh®.**
- ✓ **Colour:** natural colour liner / blue coating.
- ✓ **Sizes:** 8, 9, 10.
- ✓ **Packing:** - Cartons of 100 pairs.  - Bundles of 10 pairs.

More information: [www.singer.fr](http://www.singer.fr)



### >> Advantages

- ✓ The guarantee and benefits of an **ISO 9001** certified manufacturing: quality of products, regularity ...
- ✓ Brushed cotton liner: brings the comfort of a natural material which facilitates the absorption of perspiration
- ✓ The heavy coating provides an excellent resistance for demanding works and for jobs needing extra protection.
- ✓ Open back style allows excellent breathability.
- ✓ Anti-bacterial effect of the Actifresh® treatment deprives bacteria from developing and growing. The **Actifresh®** treatment is effective against bacteria, fungi, rust, stains and algae in preventing these micro-organisms from developing. It promotes a longer life and avoids the creation of bad odours.
- ✓ Knitted wrist securely holds the glove in place during use.

### >> Conformity

This glove has been tested as per:

- **EN 420 : 2003 +A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanical risks.

It complies with European **Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type-examination certification issued by **SATRA (Ireland)**. Notified body n°2777.

Download the EU declaration of conformity on: <http://docs.singer.fr>



EN 388: 2016. Protective gloves against mechanical risks							
Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	<b>EN 388 : 2016</b>  <b>4 1 2 1 B</b>
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>4</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>2</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>B</b>

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**



(\*) Type of use is given as a guide only. It is to the end user to check whether the product is suitable or not for the intended use. Before any use, read carefully the instructions enclosed with the product. Issue U.S.\_2019\_12\_19. Copyright: Singer, Fotolia