




TYPE A

Fully lined

With aramide
yarn

Area of use (*)



Structural work Heavy industry Finishing work

General features

- ✓ **Construction:** Gunn cut pattern. Wing thumb. Middle finger and ring finger sewn separately.
- ✓ **Material:**
 - hand (palm and back): special fire resistant treated cowhide split leather.
 - 15 cm cuff: natural split leather non heat treated.
 - aramid yarn.
 - Fully lined for enhanced protection.
- ✓ **Colour:** orange hand, grey cuff.
- ✓ **Size:** 10.
- ✓ **Packing:** Cartons of 50 pairs. Bundles of 10 pairs.

Learn more: www.singer.fr**Main advantages**

- ✓ The guarantee and benefits of an **ISO 9001** certified manufacturing: quality of products, regularity...
- ✓ Good mechanical strength and heat resistance for short contact thanks to the special treatment of leather.
- ✓ Very good resistance to the leather through a strict selection of hides.
- ✓ Wide cuff for quick removal of the glove if necessary.
- ✓ Quality of manufacture and assembly.
- ✓ Traditional leather comfort particularly appreciated for its good breathability.
- ✓ With aramid yarn for better seams strength.
- ✓ The inner lining provides better insulation against heat.

Certification

This product complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). Category II.
Issued by **INTERTEK**.

Notified body n°0362 (until 31.12.20) n°2575 (from 01.01.21).

EN 420 : 2003 +A1 : 2009
EN 388 : 2016 / EN 407: 2004
EN 12477 : 2001 + A1 : 2005

EN 388 : 2016

EN 407 : 2004



3 1 2 2 X



4 1 3 X 4 X

EN 12477 : 2001
+A1 : 2005
TYPE A

Download the EU declaration of conformity on <http://docs.singer.fr>

EN 420: 2003 + A1 2009 - PROTECTIVE GLOVES

General requirements and test methods. This standard specifies the essential requirements for ergonomics, safety, marking, information and instructions for use.

EN 388 - AGAINST MECHANICAL RISKS



1.2.3.4.F.P

1	Abrasion resistance. Level 1 to 4 (4 being the best).
2	Blade cut resistance. Level 1 to 5 (5 being the best).
3	Tear resistance. Level 1 to 4 (4 being the best).
4	Puncture resistance. Level 1 to 4 (4 being the best).
F	Cut resistance (ISO13997). Level A to F (F being the best).
P	Resistance against impact (according to EN 13594). Marking P (optional test).

For gloves that contain materials which can get dulls to the blade, and additional compulsory test must be performed according to EN ISO 13997 test method (TDM 100 tester).
This test may also be optional for gloves that do not dull the blade.

EN 374 - AGAINST CHEMICALS



Type X
X.X.X

A	Methanol	67-56-1	Primary alcohol
B	Acetone	67-64-1	Ketone
C	Acetonitrile	75-05-8	Nitrile composite
D	Dichloromethane	75-09-2	Chlorinated hydrocarbon
E	Carbone Disulphide	75-15-0	Organic compound containing Sulphur
F	Toluene	108-88-3	Aromatic hydrocarbon
G	Diethylamine	109-89-7	Amine
H	Tetrahydrofurane	109-99-9	Heterocyclic Ether
I	Ethyl acetate	141-78-6	Ester
J	n-Heptane	142-82-5	Saturated Hydrocarbon
K	Sodium hydroxide 40%	1310-73-2	Inorganic base
L	Sulphuric acid 96%	7664-93-9	Inorganic mineral acid, oxidising
M	Nitric acid (65±3) %	7697-37-2	Inorganic mineral acid
N	Acetic acid (99±1) %	64-19-7	Organic acid
O	Ammonia 25%	1336-21-6	Organic base
P	Hydrogen peroxid 30%	7722-84-1	Peroxide
S	Hydrofluoric acid 40%	7664-39-3	Inorganic mineral acid
T	Formaldehyde 37%	50-00-0	Aldehyde
	Classe 1		Breakthrough time: > 10 minutes
	Classe 2		Breakthrough time: > 30 minutes
	Classe 3		Breakthrough time: > 60 minutes
	Classe 4		Breakthrough time: > 120 minutes
	Classe 5		Breakthrough time: > 240 minutes
	Classe 6		Breakthrough time: > 480 minutes

ASTM F2878 - PUNCTURE RESISTANCE TO AN HYPODERMIC NEEDLE



Level 1	Puncture resistance with a less or an equal force to 2 N.
Level 2	Puncture resistance with a less or an equal force to 4 N.
Level 3	Puncture resistance with a less or an equal force to 6 N.
Level 4	Puncture resistance with a less or an equal force to 8 N.
Level 5	Puncture resistance with a less or an equal force to 10 N.

EN 374-5 - AGAINST MICRO-ORGANISMS



Protection against bacteria and fungi

VIRUS = with additional permeation test to virus (ISO16604)

EN 388 - AGAINST MECHANICAL RISKS



A.B.C

EN 511 - AGAINST THE COLD

A	Convective cold. Level 0 to 4 (4 being the best).
B	Contact cold. Level 0 to 4 (4 being the best).
C	Waterproofness. Level 0 (No) or 1 (Yes).

EN 407 - AGAINST THERMAL RISKS (HEAT AND/OR FIRE)



A.B.C.D.E.F

EN 12477 + A1 - FOR WELDERS

Type A	More general welding and cutting operations
Type B	Higher dexterity for TIG welding

EN 381-7 - AGAINST HAND-HELD CHAIN SAWS



Class 0	Resistance against a saw turning at 16 m/s
Class 1	Resistance against a saw turning at 20 m/s
Class 2	Resistance against a saw turning at 24 m/s
Class 3	Resistance against a saw turning at 28 m/s

Model A or B depending on the specified protection area

EN ISO 10819 - VIBRATION AND MECHANICAL SHOCKS

Hand-arm vibration. Measurement and evaluation of the vibration transmissibility from gloves to the palm of the hand.

EN 16350 - ELECTROSTATIC PROPERTIES

Each individual measurement shall satisfy: the vertical resistance requirement: $R_v < 1,0 \times 10^8 \Omega$.
Test method according to EN 1149-2: 1997.

EN 60903 - MAXIMAL TENSION OF USE

	AC	DC	Class
750 V	500 V		00
1 500 V	1 000 V		0
11 250 V	7 500 V		1
25 500 V	17 000 V		2
39 750 V	26 500 V		3
54 000 V	36 000 V		4

"X" means that the glove has not been submitted to the test.