



### >> Type of use (\*)

Thanks to its technical features, this glove is particularly suitable for all light works requiring good dexterity as well as good resistances in oily and / or fatty environments: assembly shops, automotive assembly, construction, public works, handling component parts, maintenance of public parks, gardening, painting, industrial maintenance, carpentry...

### >> General features

- ✓ **Construction, materials:** cut and sewn pattern. 100% interlock cotton liner. Light nitrile coating. Open back version. Knitted wrist. **With Actifresh®.**
- ✓ **Colour:** natural colour liner / orange coating.
- ✓ **Sizes:** 7, 8, 9, 10.
- ✓ **Packing:** Cartons of 100 pairs. Bundles of 10 pairs. 

Learn more: [www.singer.fr](http://www.singer.fr)



### >> Main advantages

- ✓ The guarantee and benefits of an **ISO 9001** certified manufacturing: quality of products, regularity ...
- ✓ Cotton interlock liner: brings the comfort of a natural material which facilitates the absorption of perspiration.
- ✓ The ultra-light coating provides an excellent softness for light handling works and offers a good grip.
- ✓ The back of the glove uncoated will allow the hand to breathe.
- ✓ Anti-bacterial effect of the **Actifresh®** treatment deprives bacteria from developing and growing. The **Actifresh®** treatment is effective against bacteria, fungi, rust, stains and algae in preventing these micro-organisms from developing. It promotes a longer life and avoids the creation of bad odours.
- ✓ Knitted wrist for a snug fit.

### >> Conformity

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.** EU type examination certificate (module B) issued by **SATRA (Ireland)**, notified body n°2777.

#### EN 388: 2016. Protective gloves against mechanical risks

Mechanical data. Information about levels.	Level 1	Level 2	Level 3	Niveau 4	Level 5	Levels ▼	<b>EN 388 : 2016</b>  <b>2 1 1 1 X</b>
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>2</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>1</b>	
Perforation resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) (as per EN ISO13997) (TDM test)	Level A	Level B	Level C	Level D	Level E	Level F	Level
	2	5	10	15	22	30	<b>X</b>

«X» means that the glove has not been submitted to the test.

Your distributor **SINGER® SAFETY**

