

15 GAUGE



**Use(\*)**

Thanks to its technical characteristics, this glove is suitable for all light and medium works in wet and/or fat/oily conditions, requiring good dexterity and protection against mechanical risks in particular abrasion: automotive assembly, precision engineering, industrial maintenance, repair of mechanical parts, electronic industry, small parts assembly...

**Technical features**

- ✓ **Construction:** seamless machine knit glove. Elasticated wrist. Open back.
- ✓ **Liner :** polyester and Elastane fibres.
- ✓ **Gauge :** 15.
- ✓ **Coating :** nitrile foam coating on palm.
- ✓ **Color :** black coating, blue liner.
- ✓ **Sizes:** 8, 9, 10, 11.
- ✓ **Packing :** - carton of 100 pairs.  
- bundle of 10 pairs.



Learn more : [www.singer.fr](http://www.singer.fr)



**Main advantages**

- ✓ The gloves are machine knitted liners made from Polyester / Elastane which gives good fit and sensitivity, superior comfort and dexterity.
- ✓ The seamless liner provides exceptional comfort and reduces hand fatigue.
- ✓ The polyester fibre offers high toughness, it provides good resistance against abrasion; it is resistant against mold and fungus. It is low water absorbent.
- ✓ Soft, foam nitrile coating on palm and polymer dots not only enhances protection but it also provides good wet grip by channeling away excess fluid from the surface.
- ✓ Glove provides good protection in dry and wet handling conditions.
- ✓ Nitrile provides good protection against oil and grease.
- ✓ Elasticated knitted wrist for a snug fit.
- ✓ The back of the glove uncoated allowing the hand to breathe.
- ✓ ISO 9001 Quality Management Standard.

**Conformity**

This glove has been tested according to the following European standards :

- **EN 420 : 2003 + A1 : 2009.** Protective gloves - General requirements and test methods.
- **EN 388 : 2016.** Protective gloves against mechanicals risks.



It complies with **European Regulation (EU) 2016/425** on Personal Protective Equipment (PPE). **Category II.**

EU type examination certificate (module B) issued by the **CTC**, notified body **n°0075**.

EN 388: 2016. Mechanical data (information about levels)	Level 1	Level 2	Level 3	Level 4	Level 5	Levels PER200	
Abrasion resistance (number of cycles)	100	500	2000	8000	-	<b>4</b>	
Blade cut resistance (index)	1,2	2,5	5,0	10,0	20,0	<b>1</b>	
Tear resistance (in Newtons)	10	25	50	75	-	<b>2</b>	
Puncture resistance (in Newtons)	20	60	100	150	-	<b>1</b>	
Cut resistance (N) as per EN ISO 13997	Level A	Level B	Level C	Level D	Level E	Level F	Level PER200
	2	5	10	15	22	30	<b>X</b>

**EN 388 : 2016**

**4 1 2 1 X**

«X means that the glove has not been submitted to the test.

Your **SINGER® SAFETY** partner

