



JUMP 750

L57012 50L

STANDARD	SIZE
S3 SRC	38/47
COLOURS	WEIGHT
Asphalt	550 gr
Black	
ELECTRIC CATEGORY	FIT
Antistatic	10,5

COMPONENTS:	
Upper:	Water-resistant nubuck and protective TPU toe-cap.
Upper lining:	Breathable mesh fabric.
Toecap:	- Aluminium toe-cap. - Impact protection 200 Joules. - Compression protection 1,500 kg.
Anti-intrusion insole:	Made of anti-perforation, absorbent, abrasion- and flakingresistant fabric.
Sole:	Made of dual-density antistatic PU directly injected onto the upper. With stabilizer for foot stability.
Tread:	High density, non-slip (SRC), abrasion- and hydrocarbonresistant.
Midsole:	Low-density, comfortable and shockproof.

MODEL DESCRIPTION:	
	Low-ankle shoe with anti-puncture fabric, water-resistant nubuck upper and protective TPU toe-cap. Breathable mesh lining. Antistatic shoe with non-slip and anti-shock sole.
RECOMMENDED USES:	
	Industry in general, engineering, construction, warehouses, agriculture.
USE AND MAINTENANCE:	
	Make sure the shoes are in good condition before each use. Take care to regularly clean them. Do not use aggressive products such as petrol, acids and solvents that could affect their quality, safety and durability.