LAVOCE CSF122.50K 12" Coaxial Speaker, Ferrite, Steel Basket Driver

Art. No.: 12603023

300 W AES LF/60 W AES HF, 8 ohms LF/8 ohms HF, 97 dB LF/105 dB HF, 45-4000 Hz LF/1000-20000 Hz HF

GTIN:







Features:

- Available in various sizes
- For further information about this product, please refer to the Data Sheet under "Downloads"

Logistic

Technical specifications:

Power:	Program: 600W LF Rated: 300W AES LF Program: 120W HF Rated: 60W AES HF
Frequency range:	45 - 4000 Hz LF 1000 - 20000 Hz HF
Sensitivity:	97 dB LF; 105 dB HF
Impedance:	8 ohms LF; 8 ohms HF
Connections:	Solder tail
Speaker:	Woofer 12" with shared ferrit magnet with dual demodulating rings Basket material: steel Conematerial: weatherproof Cardboard/paper Voice coil lows 2.5" Diaphragmmaterial: Polyamide Compression tweeter highs 1"

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

	Voice coil compression tweeter highs 1.7"
Type of speaker:	Coaxial speaker
Color:	Black
Weight:	5.60 kg

Scope of delivery:

1 x speaker

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn
All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.